

# **PASCAL600 RF Generator**

**UNIRFTECH** 

### **Pascal 600 SPECIFICATION**

## 1.Physical Specification

Item	Description
Size	485(W) x 520(L) x 132(H);Full rack size
Weight	14Kg
Rack Mount Feature	19" rack
RF Output Connector	N-Type Female
AC Power Input	VCTF-3
Chassis(EMI) Ground	4Ø Standoff
User Port Connector	25-Pin D-sub, Female
Cooling	Forced Air
RS-232	9-Pin D-sub, Female
Front Panel	LCD Display(4X20)

#### 2. Electrical Specification

Item	Description
Line Voltage	198 to 229Vac(nominal 220V $\pm 10\%$ ),3 $ \% $ no neutral connetion
Line Frequency	47 to 63Hz(50/60Hz±5%)
Line Current	5A(Single Phase)
Overcurrent Protection	15A Circuit breaker on rear panel
Power Consumption	1.1KVA nominal at full rated output
Power Factor	0.95(Min) with full rated Output into 500hm,non-reactive load
Full Rated Output Power	600W(Min) into a 50Ohm,non-reactive load
Output Power Range	1 to 600W
Frequency	13.56Mhz, $\pm 0.1\%$
Regulation	$\pm 1\%$ of setpoint or 3W(Whichever is greater) into a 50 Ohm load
Power Repeatability	$\pm 0.5\%$ of setpoints or 3W(Whichever is greater) into a 50 Ohm load

Item	Description
Response Time	<150ms for setpoints(rise/fall time from RF ON /OFF)
Reflected Power Limit	60W
Harmonics	>50dBc
Spurious Emission	>50dBc
Transient Response	Less than 0.1% change in output Power for a 10% change In the ac line voltage

#### 3. Environmental Specification

Item	Description
Temperature	+5°C to $+30$ °C( $+41$ °F to $+86$ °F) inlet temperature

#### **4.User port connector & Status Indicator**

A.User control 25-pin

NC		Signal Name	Signal Type	Remark
1		Setpoint Status	Digital Output	
2		FWD PWR Monitor	Analog Output	
3		Setpoint	Analog INput	
4		RF STATUS	Digital Output	
5		INTERLOCK	Analog Input	
6~1	13	NC		
14	1	REFL PWR Monitor	Analog Output	
15	5	RF PWR ON/OFF	Digital Input	
16	5	GROUND	GND	
17~	25	NC		

#### B. AC Power Connector Pins

NO	Description	Remark
1,2	220V (Single Phase)	
3	Frame GND	
Case	EMI shield Ground	

